



OR1000LCDRM1U Smart App LCD UPS

Cost-effective feature-rich power protection for networking, servers and telecommunications equipment.

The CyberPower Smart App LCD OR1000LCDRM1U uninterruptible power supply (UPS) with LCD panel designed for telecom equipment, and VoIP and internetworking hardware.

This UPS unit incorporates microprocessor-based digital control and includes PowerPanel® Business Edition Software providing the user unsurpassed flexibility and control.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$300,000 Connected Equipment Guarantee.

Typical Applications

- Servers
- Workstations
- Network Devices
- Telecom Equipment

Features

- 1000VA / 600W
- Line Interactive Topology
- Full AVR Buck/Boost
- GreenPower UPS™
- 1U Rack Mount
- Multifunction LCD Panel
- SNMP/HTTP Remote Management
- 6 Outlets / USB, Serial, and EPO Ports
- EMI/RFI Filters
- PowerPanel® Business Software
- 3-Year Warranty

OR1000LCDRM1U Smart App LCD UPS

Cost-effective feature-rich power protection for networking, servers and telecommunications equipment.

| GENERAL | |
|-------------------------------------|---|
| UPS Topology | Line Interactive |
| Energy Saving | GreenPower UPS™ Bypass |
| INPUT | |
| Voltage | 90Vac - 140Vac |
| Frequency | 57Hz - 63Hz |
| Plug Type | NEMA 5-15P |
| Plug Style | Right Angle |
| Cord Length | 10' |
| OUTPUT | |
| VA | 1,000 |
| Watts | 600 |
| Automatic Voltage Regulation | Yes |
| On Battery Voltage | 120Vac ± 10% |
| On Battery Frequency | 60Hz ± 1% |
| On Battery Waveform | Simulated Sine Wave |
| Outlets - Total | 6 |
| Outlet Type | NEMA 5-15R |
| Outlets - Battery & Surge Protected | 4 |
| Outlets - Surge-Only Protected | 2 |
| Overload Protection | Internal circuitry limiting / circuit breaker |
| Transfer Time | 4ms |
| BATTERY | |
| Runtime at Half Load (min) | 13 |
| Runtime at Full Load (min) | 3 |
| Battery Size | 6V/7AH |
| Replacement Battery | RB0670X4 |
| Battery Quantity | 4 |
| User Replaceable | Yes |
| Typical Recharge Time | 8 Hours |
| SURGE PROTECTION & FILTERING | |
| Surge Suppression | 1,030 Joules |
| Phone RJ11 / Ethernet RJ45 | 1-In, 1-Out (Combo) |
| EMI/RFI Filtration | Yes |
| MANAGEMENT & COMMUNICATIONS | |

| Multifunction LCD Panel | Displays: Current/Load Level, Runtime, Battery Level, Input Voltage, Output Voltage, Battery In Use, Overload, Silent Mode, Normal Mode |
|-------------------------------|---|
| HID Compliant USB Port | Yes |
| Serial Port | Yes |
| Management Cable | Serial Cable, USB Adapter |
| Audible Alarms | Input Fault, Battery Fault, Low Battery, Overload |
| Software | PowerPanel® Business Edition |
| SNMP / HTTP Remote Monitoring | Yes, with optional RMCARD205 |
| PHYSICAL | |
| Rack Size | 1U |
| Form Factor | Rack |
| Dimensions (WxHxD) (in.) | 17.25 x 1.75 x 15.75 |
| Weight (lbs.) | 35.5 |
| ENVIRONMENTAL | |
| Operating Temperature | 32°F to 95°F / 0°C to 35°C |
| Operating Relative Humidity | 0% - 95% non-condensing |
| CERTIFICATIONS | |
| Safety | UL1778, cUL 1071, FCC DOC Class B |
| Environmental | RoHS Compliant |
| WARRANTY | |
| Product Warranty | 3 Years Limited |
| Connected Equipment Guarantee | Lifetime |
| CEG Amount | \$300,000 |